

Audyn True Copper Capacitor

Order Code	Capacitance	Rated Voltage	tolerance	body diameter x length (mm)	leadout diameter x length (mm)
1501519	0.1uF	630Vdc	2%	26*36	1.5 * 65
1501520	0.22uF	630Vdc	2%	26*36	1.5 * 65
1501521	0.33uF	630Vdc	2%	33*36	1.5 * 65
1501522	0.47uF	630Vdc	2%	40*36	1.5 * 65
1501523	0.56uF	630Vdc	2%	33*51	1.5 * 65
1501524	0.68uF	630Vdc	2%	33*51	1.5 * 65
1501525	0.82uF	630Vdc	2%	40*51	1.5 * 65
1501526	1uF	630Vdc	2%	40*51	1.5 * 65
1501527	1.2uF	630Vdc	2%	50*51	1.5 * 65
1501528	1.5uF	630Vdc	2%	50*51	1.5 * 65
1501529	1.8uF	630Vdc	2%	64*51	1.5 * 65
1501530	2.2uF	630Vdc	2%	64*51	1.5 * 65
1501531	2.7uF	630Vdc	2%	74*51	1.5 * 65
1501532	3.3uF	630Vdc	2%	80*51	1.5 * 65
1501533	3.9uF	630Vdc	2%	84*58	1.5 * 65
1501534	4.7uF	630Vdc	2%	84*58	1.5 * 65