## CONTENTS - Audio Measurements by Norman H. Crowhurst - code 7003

title	page No.
Measurement techniques	7
Absolute and comparative criteria. Relative output level. Instrument	
limitations. Standards. Method of establishing equipment accuracy.	
Voltage comparisons. Waveform effects. Invalidation of reading due	
to waveform change. Loading. Spurious effects. Invalidation of read-	
ings Faults in making audio measurements. Avoiding ground loops	
and enurious officete	
and spunous enects.	
Test equipment	13
Audio oscillators. Heterodyne or heat-frequency audio oscillator. Zero	10
heat R-C feedback oscillators. Characteristics of various types of	
audio generators. Vacuum-tube voltmeters. Scales. Audio wattmeter	
Calibrated attenuators. Oscilloscopes. Square-wave generators. Har-	
monic-distortion maters. Intermodulation test meters. Wave ana-	
lyzars. Bridge circuits. Flutter and wow maters	
Basic measurements	45
Frequency. Instrument calibration. Voltage and current. Phase. Re-	
sistance and impedance. Commonly used ac bridges. Drysdale, Hay	
and Maxwell bridges. Wheatstone bridge. Direct-reading capacitance	
checker. Direct-reading impedance meter. Impedance-admittance	
bridge. Acoustic velocity and pressure. Groove velocity. Disc com-	
pliance and viscosity. Tape magnetization. Tube and transistor	
dynamic characteristics.	
Pacie amplifiere	91
Basic ampliners	01
Prequency response. Audio-oscillator comparator reconnic distortion	
Intermodulation distortion. Intermodulation tests. Hum and noise	
Measuring input impedance characteristics. Output impedance Im-	
nedance reflection. Effect of supply variation	
Output transformers	119
Specifying transformer performance. Efficiency factors. Insertion loss	
of an output transformer. Measurement of core loss. Frequency	
response. Low-frequency performance. High-frequency performance.	
Measuring magnetizing current and waveform. Leakage inductance.	
Checking winding capacitance. Notch in transformer response.	
Preamplifiers	133
Frequency response. Method for checking equalization characteristics.	100
Automatic plotting of response curves. Interaction between bass and	
treble tone controls. Variable-slope controls. Loudness contours. In-	
correct loudness compensation. Gain and sensitivity. Distortion.	
Noise. Dynamic range. Cross-talk termination. Microphony. Supply	
changes.	

Pickups and arms	151
Arm resonance. Frequency response. Pickup performance. Frequency	
discrimination. Stylus compliance. Measuring the response of a	
pickup. Shadowgraph techniques. Sensitivity. Impedance. Compli-	
ance and dynamic mass. Checking arm mechanicaf impedance char-	
acteristic. Stylus force. Distortion. A-N IM test. Utilization features.	
Counterbalanced arms.	
Turntables and changers	167
Speed constancy. Cyclic changes. Flutter and wow. Test with strobo-	
scope for speed fluctuation. Frequency test discs. Flutter and wow	
meter. Relative sensitivity of human hearing. Frequency response	
of weighting network. Rumble. Setup for testing for rumble. Vibra-	
tion pickup. Hum radiation. Measuring motor field radiation. Meas-	
uring drag produced by a tone arm.	
Tape recorders	179
Speed constancy. Varying tape tension. Flutter and wow. Method of	
preparing a standard tape for a speed constancy test. Tape handling.	
Setup for measuring start and stop times electronically. Incorrect	
alignment. Response of a good head. Frequency response. Distortion	
characteristic for a typical tape. High-frequency bias. Maximum	
density levels of different tapes. Dynamic range.	
Microphones	195
Acoustic properties. Using the Rayleigh disc. Deducing microphone	
response. Reciprocal test method. Using a calibrated microphone.	
Anechoic chamber for testing. Taking microphone response auto-	
matically. Adding a warble tone to heterodyne-type audio oscillator.	
Proximity of microphones. Symmetrical placement. Directivity.	
Transient response. Phase response. Impedance. Distortion and noise	
Vibration isolation. Effect of housing	