AUDIO SOLUTIONS A47 JUMBO SERIE





MAIN FEATURES

47 POSITIONS SHUNT TYPE AUDIO ATTENUATOR FOR LARGE SIZE THT RESISTORS

- > 47 positions, with selectable end-stops
- > Low profile; 36 mm height
- > Up to 2 channels
- > For resistors with up to 5 mm body diameter
- > Exceptional sonic performance with precise switch
- Low-bounce contact system with 3 micron gold platina
- > Motorized, IR controllable versions available
- > Free Excel resistor calculator tool available



TWO-CHANNEL VERSION

POSSIBLE CUSTOMIZATION

- PCB design and tapers
- Shafts shapes and concentric construction

TYPICAL APPLICATIONS

- Mixing desks and outboard studio equipment
- Home audio and home theater


DESCRIPTION


The A47 JUMBO audio switch series incorporates a PCB based switch contact system that is specifically designed to meet audiophile requirements for superb sonic performance.


These shunt type attenuators provide 47 positions and are available in 1 or 2 channel versions, while offering switch turning torques of 1.5, 2.5 and 5 Ncm. The PCB is designed to accommodate a maximum resistor dimension of 5 mm body diameter by 12 mm body length.

The A47 JUMBO series feature Elma's hallmark indexing feel for superior tactile feedback.

DIMENSIONS (mm)







1-wafer; L = 24.5

vw.elma.com 1,

AUDIO SOLUTIONS A47 JUMBO SERIE




PRELIMINARY


TECHNICAL DATA

| GENERAL | |
|----------------------|--|
| Indexing Resolution: | 47 positions (7.5° indexing; 345° total switch travel) |
| Switching torque: | 1.5, 2.5 or 5 Ncm (+/- 30%, over temperature range and life) |
| Rotational life: | 25k cycles (over temperature range, at 120 RPM) |
| Contact system: | Low-bounce wiper with 3 micron hard gold plated PCB |
| Resistors dimension: | Ø5 by 12 mm maximum body size, Ø1 mm maximum lead diameter |
| Taper: | Use free excel calculator to determine resistor values according to desired tapers |
| Packaging: | Single piece packed, lock washer and two nuts are included |

CIRCUITRY AND PIN ALLOCATION



TYPE KEY



ACCESSORIES TO ORDER:

| Spare nut: | P/N 5622-16 |
|---------------------------------|-------------------------|
| Stop screws (10 pcs. pack): | P/N 4124-21 |
| Free Excel resistor calculator: | Available from elma.com |

www.elma.com 2/2