

## Copper Foil Wax & Paper 100V

µF	Voltage	Diameter		Length		Cat. No.
		Inches	mm	Inches	mm	
0.01	100V	0.375	9.5	0.813	20.6	PH8001-1103J
0.10	100V	0.563	14.3	1.125	28.6	PH8001-1104J
1.0	100V	1.063	27.0	2.125	54.0	PH8001-1105J
1.5	100V	1.063	27.0	2.125	54.0	PH8001-1155J
2.2	100V	1.313	33.3	2.125	54.0	PH8001-1225J
3.3	100V	1.625	41.3	2.125	54.0	PH8001-1335J
3.9	100V	1.875	47.6	2.125	54.0	PH8001-1395J
4.7	100V	1.750	44.5	2.938	74.6	PH8001-1475J
5.0	100V	1.875	47.6	2.938	74.6	PH8001-1505J
5.3	100V	1.875	47.6	2.938	74.6	PH8001-1535J
5.6	100V	1.875	47.6	2.938	74.6	PH8001-1565J
6.0	100V	1.875	47.6	2.938	74.6	PH8001-1605J
6.8	100V	2.000	50.8	2.938	74.6	PH8001-1685J
8.0	100V	2.125	54.0	2.938	74.6	PH8001-1805J
8.2	100V	2.125	54.0	2.938	74.6	PH8001-1825J
10.0	100V	2.125	54.0	3.938	100.0	PH8001-1106J
11.0	100V	2.250	57.2	3.938	100.0	PH8001-1116J
12.0	100V	2.250	57.2	3.938	100.0	PH8001-1126J
15.0	100V	2.500	63.5	3.938	100.0	PH8001-1156J
18.0	100V	2.500	63.5	4.938	125.4	PH8001-1186J
20.0	100V	2.500	63.5	4.938	125.4	PH8001-1206J
22.0	100V	2.500	63.5	4.938	125.4	PH8001-1226J
33.0	100V	2.875	73.0	5.000	127.0	PH8001-1336J
47.0	100V	3.375	85.7	5.000	127.0	PH8001-1476J
50.0	100V	3.625	92.1	5.000	127.0	PH8001-1506J
80.0	100V	4.375	111.1	5.000	127.0	PH8001-1806J
100.0	100V	4.875	123.8	5.000	127.0	PH8001-1107J

Tolerance: +/- 5%

Operating Temperature: 80°C

Voltage: 100VDC

Dielectric: Paper & Wax

Pure Copper Foil – CDA-101

Lead wire: 99.99% Silver

0.01uf – 0.1uf = 20awg Solid

1.0uf - 18awg Solid

2.2uf and up = 3x20awg

RoHS Compliant

Made in USA

