ATTENUATOR TYPE	BODY DIMENSIONS		
	height	width	depth
Mono Series type built on a Blue 2 pole 24 way switch	40mm	45mm (	diameter
Mono Series type built on a Elma 1 pole 24 way switch	30mm	33mm	29mm
Mono Series type built on a Seiden 1 pole 23 way switch	27mm	46mm	40mm
Stereo Series type built on a Blue 2 pole 24 way switch	46mm	45mm diameter	
Stereo Series type built on a Elma 2 pole 24 way switch	45mm	33mm	29mm
Stereo Series type built on a Seiden 2 pole 23 way switch	41mm	46mm	40mm
Balanced stereo Series type built on a Blue 4 pole 24 way switch	55mm	45mm diameter	
Balanced stereo Series type built on a Elma 4 pole 24 way switch	80mm	33mm	29mm
Balanced stereo Series type built on a Seiden 4 pole 23 way switch	60mm	46mm	40mm
Mono Ladder type built on a Elma 2 pole 24 way switch	45mm	33mm	29mm
Mono Ladder type built on a Seiden 2 pole 23 way switch	41mm	46mm	40mm
Stereo Ladder type built on a Elma 4 pole 24 way switch	80mm	33mm	29mm
Stereo Ladder type built on a Seiden 4 pole 23 way switch	60mm	46mm	40mm
Stereo Series type built on a Seiden 2 pole 34 way switch	76mm	70mm	70mm
Stereo Series type built on a Seiden 2 pole 43 way switch	76mm	66mm	66mm

Sizing Chart of Glasshouse Stepped Attenuators (Using 0.5W base resistors)

please note that some additional room is required for the load resistors

When the attenuator is fitted the body dimension "height" refers to the space required from inside the front panel to the rear of the stepped attenuator.